


PORTABLE SILENCED LINE

DIESEL

**WATER COOLED ENGINE
3000 r.p.m.**



Kubota



3000
RPM



LWA
2000/14/CE
NOISE
level



WATER
cooled



DIESEL



THREE phase

MGTP 12 D AE 3F	
Code	PP130-12TS0
On board control panel equipped with:	
	<ul style="list-style-type: none"> - DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency stop - 1x16A 3Ph 400V EEC socket - 1x32A 1Ph 230V EEC socket - 1x16A 1Ph 230V EEC socket
Standard features:	
	<ul style="list-style-type: none"> - Sounproof canopy - Exhaust gas silencer
Generator	
Type	Linz E1S11M
Power	12 kVA 400V
Frequency	50 Hz
Engine	
Engine type	KUBOTA D722
N° cylinders	3
Power	17 HP
Engine speed	3000 r.p.m.
Cooling	Water
Fuel	Diesel
Starting system	Electric
Dimensions & weight	
Fuel tank capacity	37 lt
Running Time	9h
Dry weight	350 Kg
Dimensions (L. x W. x H.)	1220 x 670 x 840 mm

OPTIONS

- Site tow trailer
 Road tow trailer
 Trolley

The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.



AMIN POWER ENERGY

+48 603 442 277

+48 691 442 270

Zielone Wzgórze 6, 67-210 Głogów

biuro@powerenergy.com.pl

